



GRAVITY® LED G46

FEATURES

- SAE J581 & ECE R112 CERTIFIED STREET **LEGAL** Driving Beam: Each Light Rated at: 20-Watt; 2,300 Lumens; 1,080 LUX @ 10 Meters; 108,000 Candela
- KC's patented Gravity® Reflective Diode (GRD) system efficiently aims the LEDs back into the precision-machined reflector
- 4" x 6" Rectangular LED lights with precision machined reflector optics
- 20W per light 2 x Cree XM-L2 T6 10W LEDs
- 5,000K Color Temperature
- 50,000 Hour LED Life
- Operates on 9 to 32 Volts, EMI DO 160E Compliant
- IP68 Rated, fully self contained and sealed LED light housing
- Backed by our 23 Year Warranty
- Pair Pack Includes Wiring Harness with Waterproof Connectors, Universal U-Bracket and bolt for easy

CREE \$

PHOTOMETRICS Total beam distance with 0.25 Lux - 657m SAE/ECE CERTIFIED STREET LEGAL 1.080 lx 100M 200M **300M** 400M 6.30" 4.75" 3.85" 4.45" 1.0

KC GRAVITY® LED G46

Pair Pack	Single Light			No. of			LUX				
Part No.	Part No.	Model / Description	Beam Pattern	Watts	Amps	Volts	@10m	Lumens	Width	Height	Depth
711	1711	GRAVITY LED G46	Driving	20	3.0	9 -32	1,080	2,300	6.30"	4.75"	3.85"